


Alfred

AD-215/156**Interactive Kiosk****FEATURES**

- 21.5" or 15.6" anti-glare touch screen display (portrait or landscape)
- Floor stand, desktop stand or wall mount (VESA)
- Available for Windows, Linux Ubuntu and Android
- Built-in thermal printer and 2D barcode scanner
- ADA keypad, payment terminal brackets, LED status indicator
- Large port selection and optional Wi-Fi and BT connectivity



Alfred

Specifications



Item	AD-215 & AD-156 (Windows/Linux)	
Display	AD-215 Screen Size: 21.5", Aspect Ratio: 16:9, Resolution: 1920 x 1080, Brightness: 300 nits AD-156 Screen Size: 15.6", Aspect Ratio: 16:9, Resolution: 1366 x 768, Brightness: 220 nits AD-156 Screen Size: 15.6", Aspect Ratio: 16:9, Resolution: 1920 x 1080, Brightness: 400 nits	
Touch	PCAP touch	
CPU	Alder Lake-P Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	Elkhart Lake Intel® Celeron® J6412
Memory	DDR4 4GB, 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB	
I/O Ports	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3)	
	1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps)	
	4 x USB 3.2 + 2 x USB 2.0	3 x USB 3.2 + 3 x USB 2.0
	1 x Type-C (data transfer + display)	
	1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting	
	1 x DC +12V out	
	1 x DC +12V input	
	1 x audio (1 x line-out)	
	1 x HDMI	
Speaker	1 x speaker (3W)	
Printer	3" thermal printer	
Barcode Scanner	2D barcode scanner	
Peripheral Options	MSR, EMV terminal brackets, 5MP camera, RFID/NFC reader, ADA keypad LED status indicator (multi-colored light bar), Wheels kit: two wheels & one handle	
Mounting Options	Desktop stand, floor stand or wall mount (standard VESA)	
Wi-Fi / BT (option)	Wi-Fi 6E Intel AX210, IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2	
Operating System	1. Windows 11 IoT Enterprise LTSC (64 bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04	
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	1. S/W TPM 2.0 (BIOS)
Power Adaptor	AD-215: AC-In 100~240V / DC-Out 12V, 120W AD-156: AC-In 100~240V / DC-Out 12V, 90W	AD-215: AC-In 100~240V / DC-Out 12V, 90W AD-156: AC-In 100~240V / DC-Out 12V, 65W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (W x H x D)	Floor stand	AD-215 landscape mode: 524 x 1482 x 401 mm / 20.6 x 58.3 x 15.8 in AD-156 landscape mode: 392 x 1424 x 401 mm / 15.4 x 56.1 x 15.8 in AD-215 portrait mode: 380 x 1572 x 401 mm / 15.0 x 61.9 x 15.8 in AD-156 portrait mode: 380 x 1511 x 401 mm / 15.0 x 59.5 x 15.8 in
	Desktop stand	AD-215 landscape mode: 524 x 728 x 324 mm / 20.6x 28.7 x 12.8 in AD-156 landscape mode: 392 x 671 x 324 mm / 15.4 x 26.4 x 12.8 in AD-215 portrait mode: 324 x 818 x 324 mm / 12.8 x 32.2 x 12.8 in AD-156 portrait mode: 290 x 752 x 324 mm / 11.4 x 29.6 x 12.8 in

*Specification is subject to change without prior notice

Specifications



Item	AD-215 & AD-156 (Android)	
Display	AD-215 Screen Size: 21.5", Aspect Ratio: 16:9, Resolution: 1920 x 1080, Brightness: 300 nits AD-156 Screen Size: 15.6", Aspect Ratio: 16:9, Resolution: 1366 x 768, Brightness: 220 nits AD-156 Screen Size: 15.6", Aspect Ratio: 16:9, Resolution: 1920 x 1080, Brightness: 400 nits	
Touch	PCAP touch	
CPU	Rockchip RK3399	
Memory	LDDR4 4GB	
Storage	eMMC 32GB + 1 x micro SD card slot (up to 128GB)	
I/O Ports	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in setting (COM1, COM2) 1 x LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port supports 2 cash drawer with 24V / 12V by jumper setting 1 x DC + 12V out 1 x USB 3.0 (OTG) + 5 x USB 2.0 1 x DC +12V input 1 x audio (1 x line-out) 1 x HDMI 1 x micro SD card	
Speaker	1 x speaker (3W)	
Printer	3" thermal printer	
Barcode Scanner	2D barcode scanner	
Peripheral Options	MSR, EMV terminal brackets, 5MP camera, RFID/NFC reader, ADA keypad LED status indicator (multi-colored light bar), Wheels kit: two wheels & one handle	
Mounting Options	Desktop stand, floor stand, wall mount (standard VESA)	
Wi-Fi / BT (option)	2.4GHz/5GHz (IEEE 802.11a/b/g/n/ac), BT 4.2 (supports BLE)	
Operating System	Android 11	
TPM & vPro	N/A	
Power Adaptor	AC-In 100~240V / DC-Out 12V, 90W (AD-215) AC-In 100~240V / DC-Out 12V, 65W (AD-156)	
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (W x H x D)	Floor stand	AD-215 landscape mode: 524 x 1482 x 401 mm / 20.6 x 58.3 x 15.8 in
		AD-156 landscape mode: 392 x 1424 x 401 mm / 15.4 x 56.1 x 15.8 in
		AD-215 portrait mode: 380 x 1572 x 401 mm / 15.0 x 61.9 x 15.8 in
		AD-156 portrait mode: 380 x 1511 x 401 mm / 15.0 x 59.5 x 15.8 in
	Desktop stand	AD-215 landscape mode: 524 x 728 x 324 mm / 20.6x 28.7 x 12.8 in
		AD-156 landscape mode: 392 x 671 x 324 mm / 15.4 x 26.4 x 12.8 in
		AD-215 portrait mode: 324 x 818 x 324 mm / 12.8 x 32.2 x 12.8 in
		AD-156 portrait mode: 290 x 752 x 324 mm / 11.4 x 29.6 x 12.8 in

Contact US

*Specification is subject to change without prior notice

Partner Tech USA Inc.
 1255 N. Patt Street
 Anaheim, CA 92801
 Phone: 949-598-1888
 sales@partnertechcorp.com

Partner Tech Mexico & Latin America
 Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan
 Ciudad de México, 52764, Mexico
 Phone: 949-598-1888
 info@partnertechcorp.com

