

Audrey II

A5 II Series

Touch POS Terminal



FEATURES

- On-cell touch, optically bonded display
- Ultra-thin 7mm bezel
- 15.6" full HD with anti-glare
- High-performance Intel Tiger Lake and Elkhart Lake CPU
- Windows 10/11 and Linux Ubuntu 22.04
- High-speed M.2 PCIe SSD with up to 512 GB
- Support for Wi-Fi 6E
- Type-C connector

Audrey II

Specifications



Item	A5-2-T	A5-2-E
Size	15.6"	
Aspect Ratio	16:9	
Resolution	1920 x 1080	
Brightness	400 nits	
Touch	oTP (on-cell touch panel) Ultra-slim 7mm bezel design (with anti-glare)	oTP (on-cell touch panel) Ultra-slim 7mm bezel design
CPU	Tiger Lake UP3 Intel® Celeron® 6305 Intel® Core™ i3-1115G4 Intel® Core™ i5-1145G7, vPro Intel® Core™ i7-1185G7, vPro	Elkhart Lake Intel® Celeron® J6412
Memory	DDR4 4GB, 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB	
I/O Ports	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2)	
	1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps)	1 x LAN (IEEE 802.3 10/100/1000 Mbps)
	1 x RJ11 port with support for 2 cash drawers with 24V / 12V jumper setting	
	1 x DC + 12V out	
	4 x USB 3.2 + 2 x USB 2.0	2 x USB 3.0 + 4 x USB 2.0
	1 x DC + 12V input	
	1 x audio (1 x line-out)	
	1 x HDMI	
	1 x Type-C (data transfer + display)	1 x Type-C (data transfer only)
Speaker	1 x speaker (3W)	
Peripheral Options	MSR, EMV reader, fingerprint reader, NFC/RFID reader, 5MP camera, 2D barcode scanner, thermal printer, I/O expansion boxes (EX-100, EX-101, EX-300), printer stand, cash drawer, customer-facing displays	
Wireless (option)	Wi-Fi 6E Intel AX210, IEEE 802.11 a/b/g/n/acR2/axR2, BT5.2	
Display Support	3 independent displays (main display + HDMI + Type-C)	2 independent displays (main display + HDMI)
Spill & Dust Resistant	IP54 certified (entire unit), front panel IP65	
Operating System	1. Windows 11 IoT Enterprise GAC (64bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04	
TPM & vPro	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W	
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F	
Dimensions (W x H x D)	364 x 288 x 201 mm / 14.33 x 11.34 x 7.91 in	
Weight	5.4 kg / 11.9 lb	
Warranty	5-year standard warranty	

*Specification is subject to change without prior notice

Contact US

Partner Tech USA Inc.
1255 N. Patt Street
Anaheim, CA 92801
Phone: 949-598-1888
sales@partnertechcorp.com

Partner Tech Mexico & Latin America
Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan
Ciudad de México, 52764, Mexico
Phone: 949-598-1888
info@partnertechcorp.com

