

Receipt Printer

EVO HiSpeed Thermal

The EVO HiSpeed Thermal Receipt Printer sets the bar in both speed and reliability. Engineered to operate day-in and day-out in the harshest of environments, the EVO HiSpeed provides the steadfast performance you need. Perfect for high-volume retail and hospitality operations, the EVO HiSpeed features lightning quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.



Key Features



Print Speed

300mm/sec



Accessories Included

Power supply and interface cables included



Paper Loading

Drop-in easy thermal paper loading



AutoCutter

JamFree AutoCutter technology



Multiple Interfaces

USB, Parallel, Serial, Ethernet



Emulation

ESC/POS and OPOS compatible



Wall-Mountable

Convenient mounting capabilities

Receipt Printer

EVO HiSpeed Thermal

PART NUMBER	EVO-PT3-1HU	EVO-PT3-1HUP	EVO-PT3-1HUS	EVO-PT3-1HUE
INTERFACE SPECIFICATIONS				
Interfaces	USB	USB/Parallel	USB/Serial	USB/Ethernet
Interface Details	USB 2.0	USB 2.0/IEEE-1.284	USB 2.0/RS232C	USB 2.0/(10/100)
Emulation	ESC/POS Command Compatible			
Print Method	Direct Thermal			
Printing Speed	11.81"/sec (300mm/sec)			
Print Resolution	180 DPI x 180 DPI			
Printing Direction	Unidirectional with Friction Feed			
Sensors	Cover Open, Paper Low, Paper End			
Cash Drawer Port	1 Port, 2 Internal Circuits (24 V, 1 A max)			
Reliability	TPH Life 99.42 miles (160Km) MCBF 60,000,000 Lines			

PAPER	
Type	Thermal Paper
Width	1.9" (50mm) - 3.15" (80mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)
Roll Diameter	Max 3.27" (83mm)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14
Character/Line	Font A (12 x 24) 42 columns Font B (9 x 17) 56 columns
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)

AUTO CUTTER	
Type	JamFree auto-retracting guillotine
Life	1,500,000 Cuts
Cutting Method	Full/Partial Cut

OPTIONAL ACCESSORIES	
EVO-PT3-1CARDS	Serial Interface Card for EVO HiSpeed
EVO-PT3-1CARDP	Parallel Interface Card for EVO HiSpeed
EVO-PT3-1CARDE	Ethernet Interface Card for EVO HiSpeed

PHYSICAL	
Dimension (WxDxH)	6.1" x 8" x 6.1" (155mm x 203mm x 155mm)
Weight	3.7 lbs (1.7 kg)
Color	Black
Electrical	100-240 VAC 50/60 Hz (input) 24 VDC/1.5 A (output)

ENVIRONMENTAL		
Temperature	41°F to 104°F (5°C to 40°C) operating -4°F to 140°F (-20°C to 60°C) storage	
Humidity	35% to 80% non condensing (operation)	10% to 90% non condensing (storage)
Warranty	5-year warranty with free *2-day Advance Exchange Service	
Certifications	FCC, MIC, UL, CE, CCC, RoHs, NOM	
Operating System	WIN XP, VISTA, Win 7, WIN 8, WIN 10, OPOS drivers available	

WARRANTY EXTENSION AND UPGRADES	
ZOE-CRW3	*3-Year Overnight Exchange
ZOE-CRW5	*5-Year Overnight Exchange

*Available in USA and Canada