



The EVO TM6 touchscreen monitor features a zero-bezel design, eliminating the frame found on traditional monitors and creating a smooth, seamless, and easy-to-clean screen.



**Truflat Touchscreen**

The zero-bezel design creates a seamless, smooth surface that is easy to clean and is resistant to water, dust, grease, and food build-up, making the TM6 the ideal choice for high-traffic retail or restaurant settings.



**Ventless Design**

No vent openings also means better protection from dust and water, reaching an IP54 ingress protection rating.



**Cable-Free Accessories**

Gold contact connectors built into all accessories make for quick, simple installation. No more hassling around with tiny, internal computer connectors.



| DISPLAY        |  |
|----------------|--|
| Panel Size     | 15.0" (381mm) TFT Active Matrix          |
| Touchscreen    | Multitouch PCAP                          |
| Max Resolution | 1024 x 768                               |
| Ports          | VGA, DisplayPort, USB Type A, USB Type B |
| Brightness     | 400 nits                                 |
| Colors         | 16.7 million                             |
| Refresh Rate   | 60Hz                                     |
| Controls       | Power on/off, auto adjustment (±)        |
| Viewing Angle  | 160°                                     |

| PHYSICAL           |  |
|--------------------|--|
| Housing            | Die Cast Aluminum and ABS Plastic            |
| Weight             | 13.2lbs (6Kg)                                |
| Dimensions (WxDxH) | 14.1" x 8.2" x 14.3" (360mm x 210mm x 362mm) |
| Tilt Range         | 90° to 37°                                   |
| Housing Color      | Black  |
| Wall Mount         | 100mm VESA                                   |

| OPTIONAL ACCESSORIES     |               |
|--------------------------|---------------|
| 3 Track MSR              | EVO-MR6       |
| Fingerprint Reader       | EVO-BR6       |
| Augusta EMV Reader Mount | EVO-EMV6-AUG1 |
| 2 Line Customer Display  | EVO-RD6-LCM   |

| ELECTRICAL     |              |
|----------------|--------------|
| Adapter Output | 36W, 12V, 3A |
| Adapter Input  | 100 - 240v   |

| ENVIRONMENTAL         |                                 |
|-----------------------|---------------------------------|
| Operating Temperature | 32°F - 95°F (0°C - 35°C)        |
| Humidity              | 20% - 80% RH non-condensing     |
| Certifications        | FCC Class B, CE, LVD,           |
| IP Rating             | IP54 (Front)                    |
| Viewing Angle         | Horizontal: 140°, Vertical 130° |
| Warranty              | 3 Years                         |

| WARRANTY EXTENSION AND UPGRADES |   |
|---------------------------------|---|
| ZWE-TPC                         | 2-Year Warranty Extension                                 |
| ZOE-TPC3                        | *Next Business Day Protection                             |
| ZOE-TPC5                        | *2-Year Warranty Extension + Next Business Day Protection |

\*Available in USA and Canada.