

# TP6 Widescreen

## POS TERMINAL

### Description

With a sleek yet robust design, the EVO TP6 is the perfect enterprise-grade POS solution. The EVO TP6 features a 18.5" widescreen projected capacitive touchscreen, cable free accessories and a versatile dual hinge design.

### Highlights



#### Widescreen HD Display

The 18.5" widescreen display increases efficiency by allowing the operator to view more information on a single screen. Full 1080p HD allows for modern design and high quality images, perfect for customer facing use cases.



#### Versatile Platform

A dual hinge design allows for efficient shipping and almost unlimited tilt angles. Built-in VESA mounting extends the versatility of the platform to any wall mount installation.



#### Fan-less Design

A fan-less design provides a sleek, clean look and silent operation. No vent openings mean better protection from dust and water reaching an IP54 ingress protection rating.



#### Resilient Touch Screen

The EVO TP6 features a 18.5" widescreen LCD with projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy use.



# Specifications

MODEL	EVO-TP6W-3
Processor	Intel Core i3-6100U
Bezel	TruFlat Zero Bezel
Chip Set	Processor Integrated
System Memory	1 x DDR3L SO-DIMM 8GB
Hard Drive	2.5" 64-500GB SSD or 2.5" 500GB HDD
LCD Display	18.5" (470mm) TFT LCD
Resolution	1920x1080
Touch	PCAP, 10 Point Multi-Touch
Brightness	350 nits
Graphic Engine	Intel HD Graphics DX11 and OCL1.1
Electrical	90W/19V
Supported OS	Win 8.1 Embedded (x64), Win 8.1 Pro (x64), Win 10 IoT (x64), Win 10 Pro (x64)

PORTS	EVO-TP6W-3
USB	2 x USB 2.0 Type A / 4 x USB 3.0
Serial	3 x RJ45 with 0V/5V/12V power
LAN	1 x RJ45
Cash Drawer Port	1 x RJ11 (12V/24V)
VGA	1 x DB15

PHYSICAL	
Housing	Die Cast Aluminum
Weight	11.6 lb
Dimensions (WxDxH)	18.1" x 8" x 11.6"
Tilt	Dual Hinge
Housing Color	Black
Wall Mount	100mm VESA (75mm or 100mm with base)

OPTIONAL ACCESSORIES	
3 Track MSR	938KY430000014
Fingerprint Reader	938KY370000003
2 Line Customer Display	932AD033000233
10.1" LCD Customer Display	932AD041600233

ENVIRONMENTAL	
Operating Temperature	32°F - 95°F (0°C - 35°C)
Humidity	20% - 80% RH non-condensing
Certifications	FCC Class B, CE, LVD, NOM
IP Rating	IP54 (Front)

WARRANTY EXTENSION AND UPGRADES	
ARTFIT970	2-Year Warranty Extension
ARTFIT963	*Next Business Day Protection
ARTFIT964	*2-Year Warranty Extension + Next Business Day Protection

\*Available in USA and Canada.