

With a sleek yet robust design, the EVO TP6 is the perfect enterprise-grade POS solution. The EVO TP6 features a 15" TruFlat projected capacitive touchscreen, a range of Intel CPUs, cable free accessories and a versatile dual hinge design.



**Resilient Touch Display**

The EVO TP6 features a 15" LCD screen with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy use.



**Versatile Platform**

A dual hinge design allows for efficient shipping and almost unlimited tilt angles. Built-in VESA mounting extends the versatility of the platform to any wall mount installation.



**Fan-less Design**

A fan-less design provides a sleek, clean look and silent operation. No vent openings mean better protection from dust and water reaching an IP54 ingress protection rating.



**Efficient High Performance CPUs**

With support for Intel CPUs ranging from the efficient J1900 to the powerful Core i5, the EVO TP6 is sure to fit any application



MODEL	EVO-TP6D-F	EVO-TP6D-P	EVO-TP6D-3	EVO-TP6D-5	EVO-TP6W-3
Processor	Intel Celeron J1900	Intel Pentium 4405U	Intel Core i3-6100U	Intel Core i5-6200U	Intel Core i3-6100U
Bezel	TruFlat Zero Bezel				
Chip Set	Processor Integrated				
System Memory	1 x DDR3L SO-DIMM 4GB - 8GB			1 x DDR3L SO-DIMM 8GB	
Hard Drive	2.5" 64-500GB SSD or 2.5" 500GB HDD				
LCD Display	15" (381mm) TFT LCD				18.5" (470mm) TFT LCD
Resolution	1024x768				1920x1080
Touch	PCAP, 10 Point Multi-Touch				
Brightness	300 nits	350 nits			
Graphic Engine	Intel HD Graphics DX11 and OCL1.1	Intel HD Graphics DX12 and OCL4.2			
Electrical	65W/19V	90W/19V			
Supported OS	Win 7 Pro (x32/x64), POSReady 7(x32/x64), Win 10 IoT(x32/x64)	Win 8.1 Embedded (x64), Win 8.1 Pro (x64), Win 10 IoT (x64), Win 10 Pro (x64)			

PORTS	EVO-TP6D-F	EVO-TP6D-P	EVO-TP6D-3	EVO-TP6D-5	EVO-TP6W-3
USB	4 x USB 2.0 / 1 x USB 3.0	2 x USB 2.0 Type A / 4 x USB 3.0			
Serial	3 x RJ45 with 0V/5V/12V power				
LAN	1 x RJ45				
WLAN (Optional)	Dual Band 802.11 a/b/g/n/ac 2.4GHz/5GHz				
Cash Drawer Port	1 x RJ11 (12V/24V)				
VGA	1 x DB15				

PHYSICAL	
Housing	Die Cast Aluminum
Weight	EVO- TP6D 13.2lbs, EVO-TP6W 9.6lbs
Dimensions (WxDxH)	EVO- TP6D - 14.2" x 8" x 10.9" EVO-TP6W - 18.1" x 8" x 11.4"
Tilt	Dual Hinge
Housing Color	Black
Wall Mount	100mm VESA (75mm or 100mm with base)

OPTIONAL ACCESSORIES	
3 Track MSR	EVO-MR6
Fingerprint Reader	EVO-BR6
2 Line Customer Display	EVO-RD6-LCM
8.4" LCD Customer Display	EVO-RD6-LCD8

ENVIRONMENTAL	
Operating Temperature	32°F - 95°F (0°C - 35°C)
Humidity	20% - 80% RH non-condensing
Certifications	FCC Class B, CE, LVD, NOM
IP Rating	IP54 (Front)
Viewing Angle	Horizontal: 140°, Vertical 130°

WARRANTY EXTENSION AND UPGRADES	
ZWE-TPC	2-Year Warranty Extension
ZOE-TPC3	*Next Business Day Protection
ZOE-TPC5	*2-Year Warranty Extension + Next Business Day Protection

\*Available in USA and Canada.