

MP-4815

› Customer Display



MP-4815 supports PA-5822 POS

Features



- Ultra-thin LCD panel
- 15" backlight LCD display
- IP54 front display
- On-screen display easy to use
- Supports resistive & PCAP touch
- Different 2nd display hinge module for POS system (PA-6322, PA-6722, PA-6980, PA-6225, PA-5822 & PA-5880)
- 5M pixel USB camera module (Optional)
- 2D barcode scanner module (Optional)
- MSR / RFID / Fingerprint USB interface (Optional)

Specifications

Model	MP-4815
Customer (2nd) Display	15" XGA LCD (250 cd/m ²)
Display Resolution	1024 x 768 (XGA)
Dimensions (Panel)	367 x 37.8 x 299.3 mm (W x H x D)
Viewing Angle	Horizontal 80°, Vertical 70°
Add-ons	Max. 4-USB device support
I/O Ports	VGA DVI-I cable (support DVI-D signal only) USB
Language	English, French, Deutsch, Italiano, Spanish, Japanese, Chinese (Traditional)
Power Supply	DC12V power jack (9-16V power input)

Environment

EMC & Safety	CE / FCC
Operating Temp.	0°C~40°C (32°F~104°F)
Storage Temp.	-20°C~60°C (-4°F~140°F)
Humidity	20%~90%

Application

- Retail
- Food Service
- Information
- Hospitality

POS SKU

MP-4815 supports PA-6980 POS



MP-4815 supports PA-6225 POS



MP-4815 supports PA-6322 POS






MP-4815 supports PA-6722 POS



Dimensions

MP-4815 supports PA-6980 POS



unit: mm

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.