

# Mobilink™ P80 Plus Portable Receipt Printer

Mobile Receipt Printer

POS



## The fast, rugged, wireless, 3" receipt printer with auto cutter.

**Highly efficient** — built-in auto cutter speeds up transaction time and ensures receipts with clean, smooth edges

**Seamless integration** — compatible with iOS<sup>®</sup>, Android<sup>™</sup> and Windows<sup>®</sup> mobile devices; includes wireless setup with SimpleAP (wireless SKU only)

**Long-life battery** — operational up to 33 hours (Bluetooth<sup>®</sup>), up to 25 hours (wireless)<sup>1</sup>

**Ultra fast print speed** — prints 3" receipts at up to 100 mm per second

**Rugged design** — 4-foot drop rating, plus IP4X environmental certification

**Easy wireless configuration** — 802.11 a/b/g/n with 2.4 GHz/5 GHz compatibility, plus Bluetooth 3.0 (EDR supported)

**NFC feature** — save time with convenient touch-to-print functionality<sup>2</sup>

**Paper-saving options** — save up to 23 percent via special utility settings

**Print**

**Printing Method** Thermal  
**Print Speed** 100 mm/s  
**Print Resolution** 203 dpi  
**Print Direction** Vertical and horizontal

**Print Fonts**

**Fonts/Column Capacity** 48 cpl mode: Font A: 12 x 24 48 cpl (default); Font B: 9 x 17 64 cpl; 42 cpl mode: Font A: 13 x 24 42 cpl, Font B: 9 x 17 60 cpl  
**Character Size** 48 cpl mode: Font A 1.50 x 3.00 mm, Font B 1.125 x 2.13 mm; 42 cpl mode: Font A 1.63 x 3.00 mm, Font B 1.125 x 2.13 mm  
**Character Set** 95 Alphanumeric, 48 International, 128 x 10 Graphic  
**Barcode** UPC-A, UPC-E, JAN13/EAN13, JAN8/EAN8, Code 39, ITF, CODEBAR (NW-7), Code 93, Code 128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded  
**Two-dimensional Symbol Printing** QR Code, Maxi Code, PDF417, Composite Symbology, GS-1, Aztec, Datamatrix

**Media Handling**

**Type** Thermal roll paper  
**Paper Feed Method** Friction feed  
**Width (Without Spacer)** 3.13"/79.5 mm  
**Width (With Spacer)** 2.97"/75.5 mm  
**Paper Loading** Drop-in  
**Roll Diameter (Max)** 2.0"/51 mm  
**Core Diameter (Min)** 0.71"/18 mm  
**Paper Guide** Yes  
**Auto Cutter** Yes

**Connectivity**

**Interfaces** 802.11b/g/n (2.4 GHz) and 802.11a/n (5 GHz) or Bluetooth 3.0 (EDR supported)  
**Wireless Security Mode** WEP, WPA, WPA2-Personal/Enterprise  
**Supported Mobile Operating Systems** iOS, Android and Windows (Store Apps)  
**Easy Setting** SimpleAP, TM Utility, NFC<sup>2</sup>, and QR Code

**General**

**Printer Reliability** 10 million printing lines  
**Auto Cutter Reliability** 500,000 auto cutter  
**IP Rating** IP4X  
**Drop Rating** 4 feet  
**Charging** PS-11 charger (2.5 hours to full charge), custom single bay charger (2.5 hours to full charge), custom quad bay charger (2.5 hours to full charge)  
**Operational Battery Life**<sup>1</sup> 25 hours for wireless and 33 hours for Bluetooth  
**NV Bit Image Memory** 192KB (max), NV Graphics 384KB (max)  
**Data Buffer** 64KB (Bluetooth)  
 Notes: No information (limitation) for Wireless model  
**Printer Driver** Windows driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux), TM Virtual Port Driver, ePOS™-Print SDK  
**Software** TM-P80 Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P80 Remote Configuration Tool, TM Bluetooth Connector, Built-In Configuration Page  
**Audible Alert** Programmable Buzzer  
**LED Indicators** Blue LED (On = Power, Off = Power Off, Remaining Battery), Orange LED = Error and Battery Charging  
**Sensors** Paper End, Cover Open  
**Power Source** Custom lithium-ion battery pack, (optional) PS-11 charger  
**Power Saving** Yes  
**Temperature** 0 °C – 45 °C (without PS-11 Connection)  
**Relative Humidity** 10 – 90 %  
**Acoustic Noise Level** 55 dB  
**Standards and Approvals** North America EMI: FCC Class A, ICES-003 Class A Safety standards: UL60950-1/CSA C22.2 No.60950-1  
**Dimensions (W x D x H)** 4.3" x 5.5" x 2.7"  
 110 x 140 x 69 mm  
**Weight** 1.40 lb/630 g  
**Color** Epson Black

**Options**

**Battery** OT-BY60II  
**Single Charger** OT-SB60II  
**Quad Charger** OT-CH60II  
**Power Supply** PS-11

**Eco Features**

- Paper Saving Mode
- Power Saving Mode

**Warranty**

Standard with a 1-year limited warranty (excluding battery); optional extended warranty available (excluding battery)

**What's in the Box**

Mobilink P80 Plus, Battery – Model OT-BY60II, Roll Paper (For checking initial movement of the printer), Users Manual, USB Cable, Belt Clip – already attached to printer

**Ordering Information**

P80 PLUS WiFi Receipt with Auto Cutter C31CD70312  
 P80 PLUS BT Receipt with Auto Cutter C31CD70751



<sup>1</sup> Battery life can vary significantly depending on usage. | <sup>2</sup> NFC tag requires use of a device that includes an NFC reader, and may require additional software.

Better Products for a Better Future™  
eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806  
 Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3  
 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark. EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. ePOS and Mobilink are trademarks of Epson America, Inc. Android is a trademark of Google Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.  
 Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-51952 4/16