

## OmniLink® TM-T70-i Intelligent Printer



# The intelligent printer for mobile POS, cloud services and peripherals.

**Industry-leading front-load POS printer** — open-platform mobility for mobile POS deployments, cloud-based services, online ordering and more

**Peripheral support** - 4 USB ports for connecting up to 4 devices; easy control of peripherals through  $ePOS^{m}$  device control

**Versatile connectivity** — Ethernet and optional wireless

**Compatible** — supports Web-based printing from virtually any smartphone or tablet

**Easy implementation** — adds cloud services without the need for legacy POS integration

Fast - prints up to 170 mm/sec, supports a 3" media width

Paper-saving options — reduce your paper usage by up to 30 percent

**Comprehensive service and support** — dedicated technical resource team and customized solutions; 3-year limited warranty



### OmniLink® TM-T70-i Intelligent Printer

#### **Printing**

**Print Method** Thermal line printing Print Speed 170 mm/sec, (6.69"/sec) Fonts 9 x 17 and 12 x 24 dots/character (W x H)

Column Capacity 42/56 columns

**Character Size** 1.69 x 3.38 and 1.27 x 2.40 mm (W x H) Character Set 95 Character Alphanumeric, 48 Character International, 128 x 11 Pages Graphic

#### **Media Handling**

Media Dimensions 3.13" ± 0.02" (width) x 3.27" (roll diameter)

 $(79.5 \pm 0.5 \times 83 \text{ mm})$ 

Paper Loading 3.27" (83 mm max.)

#### **Retail-hardened PC**

Processor Intel® Atom™ ARM9 processor (400 MHz)

**System Memory 256MB** 

Operating System Embedded Linux®

Interface

USB 2.0 x 4 100 Base-TX / 10 Base-T Ethernet compliant interface VGA x 1 (D-sub 15-pin female)

#### General

#### Interfaces

Ethernet interface (100 Base-TX / 10 Base-T)

USB 2.0 Type A (4x) USB 2.0 Micro-AB

VGA x 1 (D-sub 15-pin female)

Reliability

MTBF: 360,000 hours MCBF: 52,000,000 lines Auto Cutter: 1.5 million cuts

Data Buffer 4KB or 45 bytes selectable

D.K.D. Function 2 drivers

Power Consumption Approx. 1.8 A (mean)

Power 24 Volts DC

Options Auto cutter, Near-end sensor

**Dimensions** 4.92" x 7.64" x 4.49" (125 x 194 x 114 mm)

(W x D x H)

Weight 3.97 lb (1.8 kg) Color Epson Dark Gray (EDG)

Server Systems HTTP server (Apache)

#### On board Intelligence

Intelligent Software WebPOS Configuration, ePOS-Device Standards and Approvals Safety standards: UL/CSA, RoHS and WEEE compliant

Warranty 3-year limited warranty in the U.S. and Canada

#### What's in the Box

OmniLinkTM-T70-i printer, User manual (CD), Power switch cover, Paper roll, Adapter C with AC cord, Start Here poster

#### **Eco Features**

RoHS compliant Recyclable product1

Epson America, Inc. is a SmartWay® Transport Partner<sup>2</sup>

#### **Ordering Information**

OmniLink TM-T70-i

C31C637786



1 For convenient and reasonable recycling options, visit www.epson.com/recycle | 2 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

Epson Canada Limited

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. OmniLink is a registered trademark and ePOS is a trademark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective comparts Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52078 7/16