

PA-R110

› Desktop Non-Cash Self-Payment POS

NEW



Features



- 15"/15.6" true flat touchscreen
- Embedded with 1D / 2D barcode scanner
- Embedded with 2" or 3" thermal printer
- Customizable payment terminal bracket
- Simple structure and easy maintenance

Specifications



		Valued	Performance
System	CPU Support	Intel® Celeron J1900 (2.0GHz)	Intel® Kaby Lake i3-7100U (2.4GHz) / 4415U (2.3GHz) / 3865U (1.8GHz)
	Memory	1 x DDR3L SO-DIMM socket, up to 8GB	1 x DDR4 SO-DIMM socket, up to 16GB
	Network	1 x RJ45 for 10 / 100 / 1000 Mbps	1 x RJ45 for 10 / 100 / 1000 Mbps
	Storage	1 x 2.5" HDD or SSD	1 x 2.5" HDD or SSD
	Audio	2W Speaker	2W Speaker
	USB	2 x USB 2.0, 1 x USB 3.0	1 x USB 2.0, 2 x USB 3.0
	Serial Ports (RS-232)	2 x RJ45 (5V/12V selectable by jumper setting)	1 x DB9 (5V/12V selectable by BIOS setting) 1 x RJ45 (5V/12V selectable by jumper setting)
	Display	1 x DB-15 VGA Interface	1 x DB-15 VGA Interface 1 x DP
	System Weight	System Net Weight: 16.8 kg System + Package: 19.6 kg	System Net Weight: 16.8 kg System + Package: 19.6 kg
	Dimensions (W x H x D)	382 x 642 x 279 mm	391 x 594 x 279 mm
Operating System	Windows 10 / Windows 7	Windows 10	
Power Supply	AC 100-240V available	AC 100-240V available	
Monitor	LCD	15" TFT LCD	15.6" TFT LCD
	Max. Resolution	1024 x 768	1366 x 768
	Brightness	300 cd/m ²	220 cd/m ²
	Touchscreen	Bezel-free 5-wire resistive / projected capacitive touchscreen	Bezel-free projected capacitive touchscreen
Environment	Operating Temp.	0°C~35°C (32°F~95°F)	0°C~35°C (32°F~95°F)
	Storage Temp.	-5°C~60°C (23°F~140°F)	-5°C~60°C (23°F~140°F)
	Humidity	20%~90%	20%~90%

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

Applications

- Retail
- Food Service

Highlights



* The PIN pad payment device by customer assigned.

System I/O Ports



Dimensions

