



**HIGHLIGHTS**



Projected Capacitive Touch Screen



USB MSR with Encryption (optional)



USB Touch Interface



Sleek and Stylish Design

# SPECIFICATIONS

## DISPLAY

Display Size: 15" & 17"  
Optimal Resolution: 1024 x 768 (15"), 1280 x 1024 (17")  
Panel Brightness: 350 cd/m2 (typical)  
Aspect Ratio: 4:3

## LCD PANEL

Touch: Projected Capacitive Touch Screen  
Screen: Bezel-less True Flat

## CHARACTERISTICS

Response Time: 8ms (typical)  
Tilt Angle: 0° - 70°  
Viewing Angle: 160°

## INPUT

Display Interface: VGA or Display Port  
Touch Function: USB, EETI Controller  
Speaker: x2 Standard

## POWER

Powered by a Touch Dynamic Terminal via VGA port or with external 36W Power Adapter (+12V, 3A)

## EXTERNAL I/O PORTS

USB: 2x USB 2.0  
VGA: D-SUB15 Connector  
Display Port: 1  
Audio Out: 1  
COM: 1

## ENVIRONMENT

Operating Temperature: 32° F - 104° F  
Storage Temperature: -4° F - 140° F  
Operating Humidity: 20% - 80% RH non-condensing  
Storage Humidity: 20% - 85% RH non-condensing

## DIMENSIONS

Dimension: 14.2(W) x 12.5(H) x 8.3(D) (With Base)  
Weight: 10.5lbs

## OPTIONAL PERIPHERALS

Slim MSR (encryption optional)  
Steel Coat Fingerprint reader  
Augusta reader / EMV  
2D Barcode Reader  
Pin Pad Mounts  
Wall Mount Via VESA 100x100

## INSTALLATION

Stand Alone or integrated with other Touch Dynamic products (Fully compatible with Touch Dynamic's entire product line)



## KEY FEATURES

|   |                                   |
|---|-----------------------------------|
| 1 | Projected Capacitive Touch Screen |
| 2 | Slim MSR (encryption optional)    |
| 3 | Next Generation Design            |
| 4 | Multiple Base Options             |