

## SK1-41 Series

### Four-Inch Thermal Kiosk Receipt Printer

The SK1-41 four-inch series provides dependable, maintenance-free printers that have a fast print speed of 150mm/sec with 203 dpi resolution.

Available in standard format (horizontal orientation) with and without presenter, the SK1-41 four-inch series offers a quick and reliable four-inch wide printing solution designed for servicing kiosks which provide information-intensive reports and receipts.

Easy to integrate, the SK1-41 series features two different models to accommodate any application: The SK1-41ASF4-LQ (featuring a standard paper roll holder) and the SK1-41ASF4-LQP (featuring a standard paper roll with presenter). All SK1-41 models come with RS-232C and USB interface which integrates with many commonly used kiosk solutions.

#### Features:




- Compact and Lightweight
- High Speed: 150mm/sec
- Available With and Without Presenter
- Easy to Integrate
- Adjustable Print Width: 72mm - 104mm
- Full and Partial Cut (Command Selectable)
- High Reliability: MCBF: 200 Million Pulses, Auto-Cutter: 1.5 Million Cuts

#### Ideal for the Following Industries:

- Airport
- Banking
- Cinema
- Gaming
- Gas Station
- Mass Transit
- QSR
- Ticketing
- Retail
- Time and Attendance
- Parking



# SK1-41 Series



## Specifications SK1-41

<b>Printer Method</b>	Direct Line Thermal
<b>Print Speed</b>	Max 150mm/sec
<b>Paper Width</b>	80mm, 83mm, 112mm
<b>Print Width</b>	72mm, 80mm, 104mm
<b>Paper Roll Holder</b>	120mm
<b>Resolution</b>	8 dots/mm (203dpi)
<b>Font</b>	8x16, 12x24 dots
<b>Character Types</b>	PC437 / 850 / 852 / 857 / 858 / 860 / 863 / 865 / 866, WPC 1252
<b>Bar Code</b>	JAN8/13, CODE39, ITF, CODABAR, CODE128, UPC-A/E
<b>2D Bar Code</b>	QR, Maxicode, Micro PDF-417, PDF-417, DataMatrix
<b>Interface</b>	Dual Serial (RS232C) & USB (V2.0 FULL SPEED)
<b>Cutter</b>	Full and Partial Cut (Command Selectable)
<b>Operating Voltage</b>	DC 24V
<b>External Dimensions</b>	<b>SK1-41:</b> 160.9 x 159.3 x 88.1 (w x h x d) mm
<b>Reliability</b>	<b>Max Cycles Before Failure</b> -200 Million Pulses <b>Print Head</b> -150km <b>Auto Cutter</b> -1.5 Million Cuts
<b>Safety Standards</b>	CE, FCC, VCCI

Model	Description	Part Numbers
SK1-41ASF4-LQP ST	SK1, Kiosk 4", Presenter, USB/Serial, Ext PS needed	37963690
SK1-41ASF4-LQ ST	SK1, Kiosk 4", USB/Serial, Ext PS needed	37963700



Power Adapter Cable



Power Supply